



TECHNICAL DATA SHEET
HEXA SHINE SOLID WAX

HEXA SHINE SOLID WAX



DESCRIPTION

HEXA SHINE SOLID WAX is a fast-drying, solvent-based solid wax designed to polish and restore surfaces without foot traffic, such as walls, tops, and work surfaces. Formulated with top-quality paraffin, it provides an excellent shine while enhancing the tone and appearance of treated materials. Its quick-drying action ensures fast and easy application.

Surfaces treated with **HEXA SHINE SOLID WAX** gain superior water and stain resistance, making future cleaning and maintenance much easier.

It is suitable for natural stones and also effective on cotto, terracotta, cement agglomerates, cement tiles, and terrazzo.

CHARACTERISTICS AND BENEFITS

- Brings out the natural shine of the material
- Contains premium-quality paraffin
- Quick and easy application
- Increases surface gloss
- Excellent water and oil repellence
- Makes surface maintenance easier
- Non-yellowing over time
- Fast drying
- Effective stain protection

USES

- Indoor and outdoor use.
- Suitable surfaces:
 - Marble-cement agglomerate
 - Slate
 - Basaltina - Lava stone
 - Cementina
 - Clinker
 - Cotto
 - Granite
 - Limestone
 - Marble
 - Quartzite
 - Terracotta
 - Travertine

COVERAGE

Approximately 20–25 m² per liter, depending on the surface porosity and finish.

APPLICATION EQUIPMENT

For application: Cloth, Spatula, Brush

For polishing: Orbital polisher, Flexible polisher, Arm polishing machine

APPLICATION STEPS

Preparing and cleaning the surface

- Carefully clean the surface to remove dust or dirt.
- Do not apply to wet or damp surfaces.
- For better penetration, pre-warm the surface (optional).
- Protect adjacent surfaces not being treated.

Application

- Apply an even coat with a spatula or dry cloth.
- Allow 5–10 minutes (or until completely dry).
- Polish: For small areas: Use a wool cotton cloth, white pad, or steel wool manually.
- For large areas: Use an orbital or flexible polisher with white, felt, lambskin pad, or steel wool.

- Continue polishing until excess wax is removed and an even, glossy surface is achieved.

DRYING TIME

- Fast drying: Complete within 5–10 minutes after application.
- Final drying time: No more than 5–10 hours.

PHYSICAL TECHNICAL DATA

Aspect	Paste-like emulsion
Colour	Matt or transparent (depending on the storage temperature)
Odor	Solvent
Specific Gravity at 20°C	1520 ± 20 g/l

EQUIPMENT CLEANING

Clean tools with white spirit immediately after use.

SAFETY

When applying the product, always use suitable personal protective equipment and carefully follow the instructions on the product safety data sheet.

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

INSTRUCTION AND GUIDLINES

- Never apply the product to wet or damp surfaces.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

TECHNICAL SUPPORT

Manufactured By Industrial 9-Warehouse, Behind Shirawi Enterprise, Ras Al Khor Industrial Area 2, Dubai, UAE

India Facility: 1025/1/A, Babla Compound, Gaibi Nagar, Kalyan Road, Bhiwandi, Maharashtra – 421302

www.lisauae.com | contact@lisauae.com