



TECHNICAL DATA SHEET
L-EX SHINE

L-EX SHINE



DESCRIPTION

L-EX SHINE is a solvent-based, fast-absorbing wax specially formulated to polish and enhance the color of natural stone surfaces. It can be easily applied along edges and surface irregularities. The use of L-EX SHINE enriches the shade and brightness of treated materials, while providing water and stain resistance, making daily maintenance easier.

USES

Suitable for indoor and outdoor applications on:

- Marble-concrete agglomerate
- Slate
- Basaltina (Lava stone)
- Concrete tiles
- Clinker
- Terracotta
- Granite
- Limestone
- Marble
- Quartzite
- Travertine

BENEFITS

- Easy to apply
- Provides water and stain resistance
- Enhances shade and brightness of the surface
- Does not yellow over time

COVERAGE

15–25 m² per liter (depending on material porosity and surface texture)

APPLICATION EQUIPMENT

- Application: Lambswool applicator, roller, cloth
- Polishing: Hand polisher, single-disk machine with a white pad

APPLICATION STEPS

Surface Preparation

- Clean the surface thoroughly to remove dust and dirt.
- Ensure surfaces are dry; do not apply on wet or humid surfaces.
- Heating the surface slightly may increase product penetration.
- Protect all adjacent areas not meant to be treated.

Application Process

- Always test on an inconspicuous area before full application.
- On a clean, dry surface, apply a thin and even layer with the chosen tool.
- Allow the wax to dry for approximately 12 hours.
- After drying, polish the surface using a white pad manually or with a single-disk machine.
- Polish in circular motions until residues are removed and a uniform shine is achieved.

Drying Time

- Surface drying: 5–10 minutes
- Full polishing: After 12 hours

MAINTENANCE

- L-EX SHINE maintains the brightness and finish of natural marble, granite, and concrete surfaces with easy, regular cleaning

INSTRUCTIONS AND GUIDELINES

- Avoid application on wet or humid surfaces.
- Protect areas not intended for treatment.
- Allow complete curing of adhesives or grouts before application.
- Always perform a preliminary test.

EQUIPMENT CLEANING

- Clean tools and equipment immediately after use with white spirit

TECHNICAL DATA

- Formula: Liquid
- Color: Clear
- Odor: Solvent-based
- Specific Gravity at 20°C: 1510 ± 10 g/l

STORAGE

Store tightly closed in a cool, dry place, away from direct sunlight.

SHELF LIFE

Store tightly closed in a cool, dry place, away from direct sunlight.

SAFETY

Use appropriate personal protective equipment (PPE).
Follow instructions on the Safety Data Sheet (SDS) carefully.

PACKAGING 1000 ml, 5000 ml

TECHNICAL SUPPORT

Manufactured By Industrial 9-Warehouse, Behind Shirawi Enterprise, Ras Al Khor Industrial Area 2, Dubai, UAE

India Facility: 1025/1/A, Babla Compound, Gaibi Nagar, Kalyan Road, Bhiwandi, Maharashtra – 421302

www.lisauae.com | contact@lisauae.com