



TECHNICAL DATA SHEET

LITAFILL-600

LITAFILL-600



DESCRIPTION

LITAFILL-600 is a polymer-modified, non-sanded cement-based grout ideal for filling and finishing the joints of all types of tiles, marbles, and stones. It is designed for both interior and exterior applications, offering excellent water resistance and providing strong, long-lasting joints for floors and walls.

Uses:

- Vitrified tile
- Marble
- Natural stone
- To fill the tile joints with grout so as to create strong long lasting tile joints

Key Features:

- Extra Fine Finish: Provides a smooth, refined appearance
- High Resistance to Sunlight: Maintains durability and appearance even under direct sunlight
- Easy to Clean: Simplifies maintenance with minimal effort
- High-Performance Grout: Excellent adhesion and durability
- Excellent Water Resistance: Ideal for wet areas like bathrooms and kitchens
- Natural Antibacterial Properties: Helps to maintain a hygienic surface

ADVANTAGES

- Extra fine finish
- High resistant to sunlight
- Easy to clean
- High performance grout
- Excellent water resistance
- Designed for grouting wall & floor tiles, marbles, & stones etc.
- Natural antibacterial

TECHNICAL DATA

Properties	Results
Pot life @ 20°C	4 hours
Pot life @ 20°C	3 hours
Mixed Density	1.90kg/liter (brush able Consistency)
Tensile strength	2 N/ mm ² (at 1.5mm Thickness)
Colors	Shed card available
Application temperature	Not less than 10°C
Toxicity	Non-toxic
Adhesion to Concrete	>1N/mm ²

Litafill-600 has a shelf life of 12 months if kept in a cool and dry place in unopened bags under room temperature (i.e. 27°C)

PACKAGING

- 1Kg

TECHNICAL SUPPORT

Manufactured By Industrial 9-Warehouse, Behind Shirawi Enterprise, Ras Al Khor Industrial Area 2, Dubai, UAE

India Facility: 1025/1/A, Babla Compound, Gaibi Nagar, Kalyan Road, Bhiwandi, Maharashtra – 421302

www.lisauae.com | contact@lisauae.com