



TECHNICAL DATA SHEET

POWER DARKNER

POWER DARKNER



DESCRIPTION

POWER DARKNER is a high-performance, solvent-containing treatment composed of superior synthetic resins and waxes. It enhances the color of natural and artificial stones while offering protection and ease of maintenance. It is particularly suitable for surfaces that are rough, ground, porous, or absorbent.

Key Features

- Fast drying
- Strong color intensification
- High gloss finish
- UV stable and non-yellowing
- Water and dirt resistant
- Easy to apply and maintain

APPLICATION AREAS

- Recommended for use on:
- Natural stones (marble, granite, quartzite, slate, sandstone)
- Artificial stones (terrazzo, fair-faced concrete, Solnhofen slabs)
- Ideal for corners, edges, frames, and areas that cannot be polished mechanically

Note: Not suitable for burnt products such as cotto, clinker, or stoneware

INSTRUCTIONS FOR USE

Surface Preparation:

- Ensure the surface is completely clean, dry, and free from waxes, oils, and coatings.
- Use appropriate cleaners such as Stone Cleaner, Algae and Moss Remover, or Wax Stripper as needed.
- Always rinse thoroughly with water after cleaning.

Application:

- Apply POWER DARKNER undiluted and evenly in a thin layer using a brush, paint roller, or lint-free cloth.
- Avoid applying under direct sunlight or high humidity.
- Let dry for 10 to 60 minutes depending on ambient temperature.
- For highly absorbent surfaces, a second coat may be required.

Post-application:

- Close the container immediately after use.
- Store only in its original, sealed packaging.

TECHNICAL DATA

Property	Value
Appearance	Transparent liquid
Densityapprox.	1.43 g/cm ³
Type	Solvent-based
Application Temperature Range	4°C to 40°C
Drying Time	10 to 60 minutes
Penetration	Surface level
Finish	Glossy, darkened effect

STORAGE & SHELF LIFE

- Store in a cool, dry place.
- Keep away from frost and direct heat.
- Shelf life: 24 months in unopened original container.

PACKAGING: 1000 ml | 5000 ml

SAFETY MEASURES

- Not for use on polished, glazed, or damp surfaces.
- Not scratch-proof — use with care.
- Protect surrounding materials (plastic, rubber, painted parts) during application.
- Use gloves and eye protection.
- Apply in a well-ventilated area.
- Avoid inhalation of vapors.
- Keep away from ignition sources — no smoking.
- Keep out of reach of children.
- In case of contact with skin or eyes, rinse immediately and seek medical attention.

TECHNICAL SUPPORT

Manufactured By Industrial 9-Warehouse, Behind Shirawi Enterprise, Ras Al Khor Industrial Area 2, Dubai, UAE

India Facility: 1025/1/A, Babla Compound, Gaibi Nagar, Kalyan Road, Bhiwandi, Maharashtra – 421302

www.lisauae.com | contact@lisauae.com