



TECHNICAL DATA SHEET

STAINEX+

STAINEX+



DESCRIPTION

STAINEX+ is a water-based, powerful stain remover specially formulated to tackle specific types of stains on a variety of surfaces. Its advanced formulation provides a definitive, effective solution for removing yellowing, damp stains, dark marks, stubborn stains, and colored stains. STAINEX+ can be safely applied on delicate surfaces, including polished marbles and acid-sensitive finishes, without altering their original appearance. It works independently without needing any additional products, ensuring complete stain removal.

SUITABLE FOR USE ON:

- Marble / Marble Agglomerates
- Quartz-Resin Agglomerate
- Slate
- Sandstone
- Concrete
- Craquelé and Glazed Ceramics
- Granite
- Lapped and Polished Porcelain Stoneware
- Cement Grout
- Limestone
- Exposed Brick
- Reconstituted Stone (Eco Stone)
- Quartzite
- Terracotta
- Tuff

METHOD FOR USE:

- Clean the surface to remove dust and dirt.
- If using a poultice, pour STAINEX+ into a bucket and slowly add the poultice powder while stirring until you achieve a creamy consistency.
- Apply STAINEX+ generously and evenly on the stain using a brush or spatula.
- Allow it to react according to the stain type:
 - Yellowing stains: 8–24 hours
 - Damp stains or dark marks: 8–24 hours
 - Stubborn stains: 2–8 hours
 - Colored stains: 1–6 hoursLightly scrub the surface during the reaction time if needed.
- Remove residue with a clean cloth and rinse thoroughly with water.
- Repeat the process if the stain persists.

ADDITIONAL INFORMATION:

- Apply only on dry, cool surfaces (between 5°C and 40°C).
- Avoid using on wet or overheated surfaces.
- Do not use on acid-sensitive polished surfaces.
- Protect surrounding areas not intended for treatment.
- Always test the product on a small hidden area before full application.
- If mixed with poultice, the mixture must be used within 2–3 minutes at 20°C.
- Full curing of the applied surface occurs within 15–35 minutes at 20°C (curing rate may vary with temperature).

STORAGE AND SHELF LIFE:

- Store in a cool, dry place away from direct sunlight at temperatures between 18–25°C.
- Shelf life: 24 months in original, unopened packaging

TECHNICAL SUPPORT

Manufactured By Industrial 9-Warehouse, Behind Shirawi Enterprise, Ras Al Khor Industrial Area 2, Dubai, UAE

India Facility: 1025/1/A, Babla Compound, Gaibi Nagar, Kalyan Road, Bhiwandi, Maharashtra – 421302

www.lisauae.com | contact@lisauae.com